



Maß R kann nach Bedarf ausgelegt werden

Seilrolle d1	d2	d3	d4 M7	d5	b	b1	b2	R	Lagerung	Gew. ca. kg	Bestell-Nr.		
112	131	25	47	65	18	26	30	3,5	6005.RS1	2	10.101		
		30	55	70		28	33		6006.RS1		10.102		
125	150	30	55	70	22	28	33	4,0	6006.RS1	2,5	10.103		
		35	62	80		30	35		6007.RS1		10.104		
160	188	35	62	80	26	30	35	4,8	6007.RS1	3	10.105		
		40	68	90		32,5	37,5		6008.RS1		10.106		
		50	80	105		34,5	40,5		6010.RS1		10.107		
200	235	40	68	90	26	32,5	37,5	4,8	6008.RS1	5	10.108		
		50	80	105		34,5	40,5		6010.RS1	6	10.109		
		60	95	120		33	39		45	5,3	6012.RS1	7	10.110
225	262	40	80	105	33	38,5	43,5	5,3	6208.RS1	7,5	10.111		
		50	90	115		35	43		49	6,8	6210.RS1	9	10.112
		60	110	140		39	48		54	8,0	6212.RS1	11	10.113
250	290	50	90	115	35	43	49	8,4	6210.RS1	9	10.114		
		60	110	140		39	48		54	6212.RS1	11	10.115	
		70	125	160		44	52		59	6214.RS1	13	10.116	
280	326	50	90	115	35	43	49	8,4	6210.RS1	12	10.117		
		60	110	140		39	48		54	6212.RS1	14	10.118	
		70	125	160		44	52		59	6214.RS1	16	10.119	
315	365	60	110	140	39	48	54	8,4	6212.RS1	15	10.120		
		70	125	160		44	52		59	6214.RS1	17	10.121	
		80	140	180		50	56		63	9,0	6216.RS1	19	10.122

Werkstoff: C45, 42 Cr Mo 4V. Auf Wunsch Seilrille flammgehärtet