



Maß R kann nach Bedarf ausgelegt werden
Maßänderungen und andere Lagerungen sind möglich

Seilrolle d1	d2	d3 E9	d4 K7	d5	d6 h6	b	b1	b2	R	s	t	e	Lagerung	Gew. ca. kg	Bestell-Nr.
500	570	120	210	275	140	65	125	170	12,0	130	7	3	23028	100	50.196
560	630	140	240	310	160	70	140	185	12,5	150	7	3	23032	140	50.197
630	710	160	280	350	180	75	170	215	13,5	170	7	3	23036	175	50.198
710	800	170	290	360	190	80	170	215	15,0	180	7	3	23038	220	50.199
800	900	180	310	380	200	90	180	230	17,0	190	7	3	23040	250	50.200
900	1010	200	340	410	220	100	200	250	19,0	210	10	4	23044	320	50.201
1000	1120	220	360	430	240	110	205	255	21,0	230	10	4	23048	370	50.202
1120	1250	240	400	490	260	120	225	290	25,0	250	12	4	23052	490	50.203
1250	1390	260	420	510	280	130	235	300	27,0	270	12	4	23056	600	50.204

Werkstoff: C45V, 42CrMo4V. Auf Wunsch Seilrille flammgehärtet